

FrameRelay over E1

FrameRelay-over-E1 Daemon (FRED)

Intro

- Gateway software to run on on-site E1 connection ([see article E1/T1 Interface](#))
- Bridges IPv4/IPv6/Ethernet packets between Linux kernel and FrameRelay over E1 ([RFC 2427](#), [RFC 2590](#))
- Suitable to connect [Motorola EBTS](#) (**can be used instead of Cisco routers with E1 card installed**)
- Supports FRF.12 (inner and outer) fragmentation for incoming traffic (Frame Relay -> Linux)
- Implements basic DCE-PVC LMI with support of ITU-T Q.933-A, ANSI T1.617-D, GOF (automatic detection)
- Acts via TUN/TAP network interfaces (one per DLCI) on Linux side
- Debian 12 arm64 or amd64, tested on Raspberry Pi CM4, Raspberry Pi 5

Installation

```
sudo apt install extrepo
sudo extrepo enable osmocom-latest
curl http://packages.tetrapack.online/install/tools/Debian/add-repository.sh | bash
sudo apt install -y osmo-e1d fred
```

Configuration

Default configuration file is /opt/FRED/default.env

```
#  
# Parameters for FRED binary  
  
#  
  
# E1D interface and line in format <interface number>.<line number>  
FRED_LINE=0. 0  
  
# E1 slot list in format <first slot>-<last slot>  
FRED_SLOT_LIST=1- 31  
  
# FrameRelay feature list in format <option>[,...]  
# FRF.12- OUTER - outer frame sequence counting and fragmentation (incoming frames only  
supported)  
FRED_FEATURE_LIST=  
  
# DLCI list in format <DLCI>: <type>[,...]  
# LMI-DCE-PVC  
# IP - IP bridge (RFC 2427 for IPv4, RFC 2590 for IPv6)  
# ETH - Ethernet bridge (RFC 2427)  
FRED_DLCI_LIST=0: LMI-DCE-PVC, 16: IP, 17: IP  
  
# Path to configuration script to manage IP interface configuration on up and down  
FRED_SCRIPT=. /dimetra-hook.sh  
  
#  
# Parameters for dimetra-hook.sh  
  
#  
  
# Zone ID  
DIMETRA_ZONE=1  
  
# Local Site ID  
DIMETRA_SITE=12  
  
# FrameRelay DLCIs  
DIMETRA_DLCI_PRIMARY=16  
DIMETRA_DLCI_SECONDARY=17
```

```
# When set, routes will be added to FRR's OSPF prefix list  
FRR_PREFIX_LIST=dimetra
```

Use with Dimetra

FRED package includes prepared scripts to establish connection between EBTS and Dimetra MPVPN network.

```
sudo /opt/FRED/dimetra-setup.sh
```

Best settings for EBTS TSC will be:

```
.sitelink -e1  
.e1config -crdStart 1 -crd 31 -ts16Skip off -portNo 1 -crc on  
reset
```

Multiple instances

You can have several separated systems connected to a local Linux system. For such case you need to have several .env files for each configuration. use *sudo ./setup.sh install* to register all instances.

Also it's possible to run FRED in command line - *sudo ./run.sh <configuration.env>*

Revision #32

Created 15 December 2023 21:27:08 by R3ABM

Updated 5 January 2024 11:09:41 by R3ABM